

TECHNICAL DATA : SMV 28-1200 B

LIFTING DATA		
Lifting capacity / Load center (up to 9000 mm / standard mast)	kg / mm	28000 / 1200
Lifting speed, unloaded / at rated load	m/s	0,32 / 0,27
Lowering speed, unloaded / at rated load	m/s	0,40 / 0,40
DRIVING DATA		
Drive speed forward, unloaded / at rated load	km/h	24 / 23
Drive speed reverse, unloaded / at rated load	km/h	24 / 23
Incline (driving ability) at rated load at 0 km/h/at 2 km/h	%	33 / 22
Towing (power ability) at rated load at 0 km/h/at 2 km/h	kN	225 / 156
SERVICE WEIGHT / AXLE PRESSURE		
Service weight	kg	39600
Axle pressure front, unloaded / at rated load	kg	20300 / 63100
Axle pressure rear, unloaded / at rated load	kg	19300 / 4500
ENGINE (electronic controlled)		
Engine make / model name		Volvo TAD-722-VE/HT
Emission approval EU / US		St II / Tier 2
Monitoring / emission controlled / CanBus		Yes / yes / yes
Fuel / type of engine / intercooler		Diesel/4-stroke/ yes
Power ISO 3046 / at speed	kW / rpm	180 / 2300
Torque ISO 3046 / at speed	Nm / rpm	1050 / 1400
Displacement / No. of cylinders / type	L / /	7,2 / 6-cyl / Inline
Fuel consumption, normal driving	L/h	10 – 13
Alternator, type/power	W / Amp	AC / 1540 / 55
Starting battery, voltage/capacity	V / Ah	2 x 12 / 140
TRANSMISSION (electronic controlled)		
Transmission make / model name		Dana TE-17300
Monitoring / reverse protection / CanBus		Yes / yes / yes
Clutch, type		Torque converter
Transmission type / type of shift gear		Softshift – Powershift / Automatic
No. of gears, forward/reverse		3 / 3
DRIVE AXLE & STEER SYSTEM		
Drive axle make / model name		Kessler D91
Drive axle type / drive axle width	/ mm	Differential + hub reduction / 3440
Service brake system, type / affected wheels		Oil cooled Wet Disc Brakes / drive wheels
Parking brake system, type / affected wheels		Dry disc brake / spring release / drive wheels
STEER AXLE & STEER SYSTEM		
Steer axle make / type		Konecranes / double acting single cylinder
Steering system		Hydraulic servo assisted / power steering
WHEELS		
Number of wheels, front+rear / Type (*driven)		4*+2 / pneumatic
Tire pressure front / rear	MPa	0,9 / 0,9
Tire dimensions (Ply rating) front / rear	Inch (No)	16.00 x 25" (PR 28) / 16.00 x 25" (PR 28)
Rim dimension front / rear	Inch	11.25 x 25" / 11.25 x 25"
HYDRAULIC SYSTEM		
Hydraulic pump make / model name		Parker & Hannifin / P2-series
Hydraulic system / pump type		Load sensing system / variable piston pump
Power-on-demand / Low energy		Yes / yes
Hydraulic oil pressure mast	MPa	20
TANK VOLUMES		
Diesel tank volume	L	316
Hydraulic tank volume	L	355
LIFTING EQUIPMENT		
Lift mast make / model		Konecranes / Duplex standard
Lift mast type / design		2-stage / free visibility
Fork carriage make / model		Konecranes / integral double forks
Fork carriage type		Hydraulic side shift & fork positioning
OTHERS		
Noise level (inside Cab / Lm) DIN 45635	dB(A)	70
Noise level (inside Cab/ LpAZ) EN 12053	dB(A)	75
Noise level (outside at 7 m/ Lwa) 2000/14/EC	dB(A)	110
NORMS & STANDARDS		
Machine Directive in Europe	98 / 37 EC	Yes
Stability of Industrial Trucks	ISO 1074	Yes
Safety of Industrial Trucks	EN 1551	Yes

TECHNICAL DATA

SMV 28-1200 B

